

TRAFFIC CONTROL METHOD, NETWORK SYSTEM
AND FRAME RELAY SWITCH

BACKGROUND OF THE INVENTION

INSAI

1. Field of the Invention

5 The present invention relates to a network system
in which plural frame relay networks are connected to an
ATM (Asynchronous Transfer Mode) switch, to a traffic
control method in the network system and to a frame
relay switch in each of the plural frame relay networks.

10 2. Description of the Related Art

Recently, the B-ISDN (Broadband Integrated Service
Digital Network) is rapidly introduced as the LAN (Local
Area Network) is made a high speed and a multimedia. In
data communication, as a first step for the next
15 generation, cases increase in that an ATM network is
used as a repeater for frame relay networks.

FIG. 16 is a whole structural view of a network
system which an ATM network is used as a repeating
network for plural frame relay networks. In FIG. 16,
20 frame relay networks 1, 2 are respectively connected
with an ATM network 3 through each IWF (InterWork
Function) 4 which disassembles a frame into cells. The
frame relay networks 1, 2 are also respectively
connected with terminals 5, 6 for users in the network
25 system. In the ATM network, a VP (Virtual Path) which
plural VCs (Virtual Channel) are put together is set,
and communication channels (VCC: Virtual Channel

09467004 011000

Connection) for respective VCs are set. A maximum transmission rate (PCR: Peak Cell Rate) which cells can be transmitted is also set every VCC. Then, when a number of cells transmitted from the IWF 4 to the ATM network 3 exceeds the PCR set for the ATM network 3, the ATM network 3 discards cells so as to avoid or release congestions in the ATM network 3. When a cell (frame) is discarded in the ATM network 3, no response frame to the discarded cell (frame) is transmitted to the terminals 5, 6. Thus, when the user of terminal 5 or 6 receives no response frame concerning the frame transmitted by the user for a predetermined time, the user determines that no frame reaches a transmitted terminal, and transmits the same frame as said discard cell (frame) again.

The above-described network system, however, has the following problems.

That is, a number of cells transmitted from the IWF 4 to the ATM network 3 exceeds the PCR, whereby cells (transmitting frames) are frequently discarded. Thus, the terminal 5 or 6 which has transmitted the discarded frame (cell) re-transmits the transmitting frames frequently, As the result, there was a possibility in that congestions occur in the frame relay networks FR1, FR2, too.

Further, frames are re-transmitted from the terminals 5, 6 caused by that cells (frames) are discarded in the ATM network 3, whereby processes

increase in the frame relay networks FR1, FR2. Thus, there was a possibility in that a response deteriorates between the terminal 5 and the terminal 6 (end to end).

SUMMARY OF THE INVENTION

5 Accordingly, it is an object of the present invention to solve the above described problems, and to provides a traffic control method, a network system and a frame relay switch, wherein it is possible to prevent a number of cells in an ATM network from exceeding a
10 maximum transmission rate (PCR).

 The present invention introduces the following structure to solve the above described problems.

 That is, the preset invention relates to a traffic control method in a network system. The network system
15 comprises an ATM (Asynchronous Transfer Mode) network, plural frame relay networks respectively connected to the ATM network through channels and plural terminals respectively connected to the plural frame relay networks through channels. In this traffic control
20 method, a data quantity transmitted through each channel is measured, a traffic restrictive level corresponding to the data quantity which is measured is operated, and a traffic restrictive process corresponding to the traffic restrictive level which is operated is performed
25 (first aspect).

 According to the traffic control method in the

09481001 011000

present invention, for example, when data is transmitted from the frame relay network to the ATM network, a data quantity is measured in the frame relay network connected with the transmitted terminal of the data, the traffic restrict level is operated in accordance with this data quantity, and the traffic restrict process is performed. Thus, the data quantity can be controlled within a desired range.

The data quantity may be measured when the frame relay network transmits a frame or receives a frame.

Any number of steps (levels) may also set as the traffic restrictive level when necessary. The measuring time of the data quantity can be varied suitably, namely, may be fixed or may be varied in accordance with the congestion condition in the network system.

The traffic restrictive process may comprise a process for writing information indicating that a congestion occurs to data transmitted through the each channel (fourth aspect). For example, "1" is set into a FECN (Forward Explicit Notification-bit) stored in a core header of the frame to be data, the transmitted terminal of the frame receives the frame of which the FECN stored in the core header, whereby a congestion control is performed (such as the frame transmission to the frame relay network is controlled or stopped). "1" is set into a BECN (Backward Explicit Notification-bit) stored in a core header of the frame to be data, the

transmitted terminal of the frame receives the frame of which the FECN stored in the core header, whereby a congestion control is performed.

5 The traffic restrictive process may comprise a process for discarding data transmitted through the each channel.(fifth aspect).

10 The traffic restrictive process may comprise a process for transmitting a message indicating that a congestion occurs to a transmitting terminal of data transmitted through the each channel (sixth). For example, a CLLM (Consolidated Link Layer Management) message is transmitted to the transmitted terminal of the frame to be data, the transmitted terminal of the frame receives the CLLM message, whereby a congestion
15 control is performed.

One of the above-mentioned traffic restrictive processes may be performed, and the plural traffic restrictive processes may be also performed synchronously. The correspondence between the traffic
20 restrictive level and the traffic restrictive process can be set suitably.

The traffic restrictive process may be performed based on a maximum transmission rate set for the each channel (seventh aspect).

25 In the traffic control method of the present invention, the data quantity may be measured as to data transmitted from each of the plural frame relay networks

09481001.011000

to the ATM network through the each channel (second aspect).

In the traffic control method, a traffic restrictive class set for the each channel may be detected, and the traffic restrictive process corresponding to the traffic restrictive class which is detected may be performed. In this case, the traffic restrictive process can be performed in accordance with the importance of the channel, therefore, channels can be discriminated. Any number of channels can be available, and the channels include a physical channel, a virtual channel, a logical channel (data links) and so on. The traffic restrictive classes can be set at any number of steps.

At least one of the plural terminals may be connected to the ATM network through no frame relay network (eighth aspect).

The present invention also relates to a network system comprising an ATM (Asynchronous Transfer Mode) network, plural frame relay networks respectively connected to the ATM network through channels, plural terminals respectively connected to the plural frame relay networks through channels, a data quantity measurement unit for measuring a data quantity transmitted through each channel, a restrictive level operation unit for operating a traffic restrictive level corresponding to the data quantity measured by the data

09491001 011000

quantity measurement unit, a restrictive process storage unit for storing a traffic restrictive process corresponding to the traffic restrictive level operated by the restrictive level operation unit, and a traffic control unit for reading the traffic restrictive process corresponding to the traffic restrictive level operated by the restrictive level operation unit from the restrictive process storage unit and for performing the traffic restrictive process read from the restrictive process storage unit.

The present invention relates to a frame relay switch in plural frame relay networks in a network system comprising an ATM (Asynchronous Transfer Mode) network, the plural frame relay networks respectively connected to the ATM network through channels and provided with plural frame relay switch, and plural terminals respectively connected to the plural frame relay networks through channels. The frame relay switch comprises a data quantity measurement unit for measuring a data quantity transmitted through each channel, a restrictive level operation unit for operating a traffic restrictive level corresponding to the data quantity measured by the data quantity measurement unit, a restrictive process storage unit for storing a traffic restrictive process corresponding to the traffic restrictive level operated by the restrictive level operation unit, and a traffic control unit for reading

09481001-011000

the traffic restrictive process corresponding to the traffic restrictive level operated by the restrictive level operation unit and performing the traffic restrictive process read from the restrictive process storage unit.

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects and advantages of the present invention will become apparent during the following discussion conjunction with the accompanying drawings, in which:

FIG. 1 is a whole structural view of a network system according to an embodiment of the preset invention;

FIG. 2 is an explanatory view of channels in the network system shown in FIG. 1;

FIGs. 3(a) and 3(b) are structural views of a frame and a cell;

FIG. 4 is a circuit structural view of a frame relay switch shown in FIG. 1;

FIG. 5 is a block diagram illustrating functions implemented by performing a control program in the frame relay switch shown in FIG. 4;

FIG. 6 is a structural view of a restrictive class management table shown in FIG. 5;

FIG. 7 is a structural view of a restrictive threshold management table shown in FIG. 5;

FIG. 8 is a structural view of a transmission data cumulative table shown in FIG. 5;

FIG. 9 is a structural view of a transmitted frame relay network number retrieval table shown in FIG. 5;

5 FIG. 10 is a structural view of a task number storage table shown in FIG. 5;

FIG. 11 is a flow chart illustrating a process by a frame relay switch shown in FIG. 1;

10 FIG. 12 is a flow chart illustrating a process by a frame relay switch shown in FIG. 1;

FIG. 13 is a flow chart illustrating a process by a frame relay switch shown in FIG. 1;

FIG. 14 is a flow chart illustrating a process by a frame relay switch shown in FIG. 1;

15 FIG. 15 is a sequence diagram illustrating an operational sample of the network system shown in FIG. 1;

FIG. 16 is a whole structural view of the network system shown in FIG. 1; and

20 FIG. 17 is a view for explaining an outline of a traffic restrictive process in the network system.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Detailed explanations will be given of a traffic control method, a network system and a frame relay switch according to the present invention based on a preferred embodiment shown in drawings.

25

09481001.011000

First, an explanation will be given of an outline of the network system according to this embodiment with reference to FIGs. 1, 2. FIG. 1 is a whole structural view of the network system according to this embodiment.

5 In FIG. 1, an ATM network 20 is connected with three frame relay networks FR1, FR2, FR3 via IWFs (InterWork Function) 21a-21c, respectively. The frame relay networks FR1, FR2, FR3 are respectively connected with plural frame relay terminals (hereinafter, simply called
10 "terminal") 22a-22h.

The ATM network 20 is provided with plural ATM switches (VCH, VPH) not shown and repeats a frame F (see FIG. 3(a)) between the frame relay networks FR1, FR2, FR3 by using a cell S (see FIG. 3(b)). The IWFs 21a-21c
15 are repeaters for changing a frame F transmitted from one of the frame relay networks FR1-FR3 connected thereto into cells S (see FIG. 3(b)) so as to transmit the cells S to the ATM network 20 and for assembling cells S received from the ATM network 20 into a frame F
20 so as to transmit the frame F to one of the frame relay networks FR1-FR3 connected thereto. The respective frame relay networks FR1-FR3 is provided with plural frame relay switches 31 connected through frame relay circuits (physical channel). The respective terminals 22a-22h are
25 respectively connected with one of the frame relay switches 31a-31f via the frame relay circuits in the respective frame relay networks FR1-FR3. Each terminal

09491001, 011000

22a-22h, when data is transmitted to another terminal, generates a frame F and transmits it to one of the frame relay switches 31a-31f connected thereto.

FIG. 2 is an explanatory view of channels set in the network system shown in FIG. 1. In FIG. 2, four data links (logical channels) connecting the IWF 21a and the respective terminals 22a-22d are set in the physical channel (frame relay circuit) connecting between the terminals 22a-22d and the IWF 21a. Then, DLCI (Data Link Connection Identifier) numbers a-d are respectively set for the data links (hereinafter, respective data links are called "DLCIa, DLCIb, DLCIc, DLCId"). Similarly, the terminal 22e and the IWF 21b are connected via the data link of the DLCI number e (hereinafter, called "DLCIe"), and the terminal 22f and the IWF 21b are connected via the data link of the DLCI number f (hereinafter, called "DLCIf"). Moreover, the terminal 22g and the IWF 21c are connected via the data link of the DLCI number g (hereinafter, called "DLCIg"), and the terminal 22h and the IWF 21c are connected via the data link of the DLCI number h (hereinafter, called "DLCIh").

In FIG. 2, two VCs (Virtual Channels) are set between the IWF 21a and the ATM network 20, and a not shown VP (Virtual Path) in which these VCs are put together is also set therebetween. A $VCCx_1$ and a $VCCx_2$ which are VCCs (Virtual Channel Connections) of the respective VCs are also set. The $VCCx_1$ is connected with

09481001 "011000"

5

20

25

5

10

15

25

terminal (transmitted terminal) by identifying plural data links (logical channels) set in this network system. The frame F is transmitted through the data link having the DLCI number corresponding to the DLCI number stored in itself (the frame F). The FECN is information (bit) for informing that a congestion avoidance procedure is necessary for a transmitted terminal of the frame F. The BECN is information (bit) for informing that a congestion avoidance procedure is necessary for a transmitting terminal of a frame F. The FECN and the BECN are usually set to "0", and, when a congestion occurs, are changed to "1" in the frame relay network (frame relay switch) which the congestion occurs. The DE is information whether the frame F must be discarded in taking priority over another frame or not, and when the DE is "1", the frame is discarded in taking priority. In the data part 28, user communication data of the terminals 22a-22h and the like are stored. In the FCS 29, information for detecting an error of the frame F is stored. Further, the head and tail of the frame F can be recognized by the head flag 25 and the tail flag 30.

In FIG. 3(b), the cell S is provided with a cell header 70 of 5 octet and a data part 71 of 48 octet. In the cell header 70, a VPI (Virtual Path Identifier), a VCI (Virtual Channel Identifier) and the like are stored. The VPI and the VCI are identifiers for selecting a communication path (VCC) for the cell S. The

09401001 011000

VPI and the VCI are identified in the IWFs 21a-21c and the ATM network 20, whereby the cell S is transmitted via a suitable communication path (VCC). The data part 71 is an area for storing communication data of the terminals 22a-22h and so on. When a frame F is disassembled into cells S in the IWFs 21a-21c, the core header 28 and the data part 28 of the frame F are divided per 48 octet, each part of divided frame becomes a content of the data part 71 in the cell S. Then, the cell header 40 is added to each part of divided frame, whereby plural cells are formed.

Next, an explanation will be given of an outline of the traffic restrictive process in this network system with reference to FIG. 17.

FIG. 17, in relation to the restrictive classes and the restrictive levels, shows traffic restrictive processes (restrictive tasks) which are preformed on the basis of combinations of the restrictive classes and the restrictive levels. As shown in FIG. 17, for each restrictive level, a condition expression to be that restrictive level is set as follows. Concretely, a condition expression which a restrictive level becomes non-restriction (expression 1), a condition expression which a restrictive level becomes a first restriction (expression 2), a condition expression which a restrictive level becomes a second restriction (expression 3), a condition expression which a

When a restrictive level is the first restriction, in each frame relay network FR1-FR3, "1" is set into the FECN in the core header 27 (see FIG. 3(a)) of a frame F to be transmitted (process task (2)) and "1" is set into the BECN in the core header 27 of a received frame F (process task (5)). When a restrictive level is the second restriction, in each frame relay network FR1-FR3, when "0" is set in the DE of the core header 27 of a frame F to be transmitted, "1" is set into the FECN of the frame F, and when "1" is set in the DE, the frame F is discarded (process task (3)). The above-mentioned process task (5) is also performed for the received frame F. When a restrictive level is the third restriction, in each frame relay network FR1-FR3, the same traffic restrictive process as the second restriction, namely, the process task (3) and the process task (5) are performed. When a restrictive level is the fourth restriction, in each frame relay network FR1-FR3, the transmitted frame is discarded (process task (4)), and the above-mentioned process task (5) is performed.

Further, when the restrictive class is the important class, the following traffic restrictive process is performed in accordance with the restrictive levels. That is, when a restrictive level is non-restriction or the first restriction, the process task (1) is performed, namely, no traffic restrictive process

is performed. When a restrictive level is the second restriction, in each frame relay network FR1-FR3, the process task (2) and the process task (5) are performed. When a restrictive level is the third restriction, in
5 each frame relay network FR1-FR3, the process task (3) and the process task (5) are performed. When a restrictive level is the fourth restriction, in each frame relay network FR1-FR3, the process task (4) and the process task (5) are performed.

10 Moreover, when the restrictive class is the most important class, the following traffic restrictive process is performed in accordance with the restrictive levels. That is, when a restrictive level is non-restriction or one of the first-third restrictions, the
15 process task (1) is performed, namely, no traffic restrictive process is performed. When a restrictive level is the fourth restriction, in each frame relay network FR1-FR3, the process task (4) and the process task (5) are performed.

20 Next, an explanation will be given of frame relay switches 31a-31i in the respective frame relay networks FR1-FR3. FIG. 4 is a sample of a circuit structural view of each frame relay switch 31. Each frame relay switch 31a-31i has the same structure, therefore, the
25 explanation is given by using the frame relay switch 31g as a sample. In FIG. 14, the frame relay switch 31g is provided with a management processor unit 32 and a

094431001-011000

circuit dealing unit 41.

09441001 " 0110000

The management processor unit 32 performs the control and the monitor all over the frame relay switch 31, the maintenance and management for various data, the

5 input/output control for commands and messages, the making and the keeping of connection records and the like. The management processor unit 32 is provided with an active CC (Central Controller) 33a, a spare CC 33b, an active MM (Main Memory) 34a connected with the CC 33a

10 via a bus, a spare MM 34b connected with the CC 33b via a bus, an active CHCs (Channel Controller) 35a, 35b respectively connected with the CC 33a via buses, a spare CHCs 35c, 35d respectively connected with the CC 33b via buses, SIAs (Serial Interface Adapter) 36a, 36b

15 and IOCs (disk Input Output Controller) 37a, 37b respectively connected with the CHCs 35a, 35d via buses, a system console 38 connected with the SIA 36a, hard disks 39 respectively connected with the IOCs 37a, 37b, and a MO (Magnetic Optical disk) 40 connected with the

20 IOC 37a.

The hard disk 39 is a medium storing a control program (computer program) for the frame relay switch 31g and data to perform the control program. The

respective MMs 34a, 34b are operating areas for the CCs

25 33a, 33b, and when the CCs 33a, 33b perform the control program stored in the hard disk 39, the control program is loaded to the MMs 34a, 34b. The CCs 33a, 33b perform

the control programs respectively loaded to the MMs 34a, 34b, and send commands to the respective parts in the frame relay switch 31g to perform the operational control for the respective parts.

5 The respective CHCs 35a-35d perform the control of the input output channel (physical channel, logical channel) and the control of the data transfer with the MMs 34a, 34b in accordance with the commands from the respective CCs 33a, 33b. The IOCs 37a, 37b control the
10 operations of the hard disks 39 and the MO 40 in accordance with the commands from the respective CCs 33a, 33b. The MO 40 functions as an external unit of the frame relay switch 31g and performs the loading of the initial program, the drawing up of data and the like.

15 The system console 38 is an interface for outputting data stored in the hard disks 39 and the MO 40, performed results in the CCs 33a, 33b and so on to the outside, and for inputting data, commands and so on from the outside.

20 The circuit dealing unit 41 is a CMU (Communication Multiplexer Unit) accepting plural circuits (physical channel, virtual channel, logical channel). The circuit dealing unit 41 is provided with MPs (line Management Processor) 42 respectively connected with the CHCs 35b,
25 35c via buses, plural pairs of LCs (Line Controller) 43a (active), 43b (spare) respectively connected with the MP 42 via a bus, and plural LSW (Line Switch) 44 connected

09481001 "011000

with the respective pairs of the LCs 43a, 43b.

Each LSW 44 accepts plural circuits (physical channel) and receives the frame F transmitted from the outside. Each LSW 44 also transmits the frame F received
5 from the LC 43a or the LC 43b to suitable circuits. At that time, each LSW 44 transmits the frame F to the circuits corresponding to commands from the MP 42. Moreover, the LSW 44 receives the commands from the MP 42 via each LC 43a, 43b, and controls logical,
10 electrical and physical interfaces in accordance with those commands.

The LCs 43a, 43b perform a frame relay protocol process. The LCs 43a, 43b, when receive a frame F from one of LSWs 44, send the frame F to the MP 42. The LCs
15 43a, 43b also send the frame F received from the MP 42 to one of the LSWs 44. Further, the LCs 43a, 43b are provided with circuit end functions for making the plural circuits end.

The MP 42 manages the line setting in the line
20 dealing unit 41. That is, the MP 42 controls the communications between the CHCs 35b, 35c and the LCs 43a, 43b, respectively. Concretely, one of each pair of the LCs 43a, 43b is made in an operating status (active) and the other is made in a stopping status (spare). The
25 MP 42, when receives a frame F from the active LC 43a, sends the received frame F to the active CHC 35b. In this way, the frame F is stored in the active MM 34a,

09483001-01000

5

10

20

25

5

10

20

and the DLCI corresponding to the transmitted frame relay network number as retrieval keys.

FIG. 7 is a structural view of the restrictive threshold management table 51. In FIG. 7, values for
5 operating the above-mentioned restrictive levels are stored in the restrictive threshold management table 51 every transmitted frame relay network number.

Concretely, the allowable maximum transmission rate (maxR), the measuring time (t1) and the first-fourth
10 restrictive coefficients (n1-n4) are stored in the restrictive threshold management table 51 every transmitted frame relay network number. The restrictive threshold management table 51 can be retrieved by using the transmitted frame relay network number as a
15 retrieval key.

FIG. 8 is a structural view of the transmission data cumulative table 52. In FIG. 8, a cumulative transmission data quantity (SD2) and one of the above mentioned restrictive levels are stored in the
20 transmission data cumulative table 52 every transmitted frame relay network number. The transmission data cumulative table 52 can be retrieved by using the transmitted frame network number as a retrieval key.

FIG. 9 is a structural view of the transmitted frame relay network number retrieval table 53. In FIG.
25 9, a transmitted frame relay network number is stored in the transmitted frame relay network number retrieval

09461001-01000

table 53 every DLCI number. The transmitted frame relay network number retrieval table 53 can be retrieved by using the DLCI number as a retrieval key.

FIG. 10 is a structural view of the task number storage table 54. In FIG. 10, the task number storage table 54 is provided with a transmitting process task storage area 54a and a receiving process task storage area 54b. Each storage area 54a, 54b is divided into three class areas 59 corresponding to the above mentioned three restrictive classes, and the above-mentioned process tasks (1)-(5) are stored in each class area 59 in relation to the restrictive levels. The task number storage table 54 can be retrieved by using process identifier information (transmitting process information (bit "0"), receiving process information (bit "1")) indicating that one of the transmitting process and the receiving process is performed, a restrictive class and a restrictive level as retrieval keys. That is, one of the transmitting process task storage area 54a and the receiving process task storage area 54b is selected by the process identifier information, one of the class areas 59 is selected by a restrictive class, and one of the process tasks (1)-(5) is read by a restrictive level so as to correspond to that restrictive level.

The frame transmission processing part 55 shown in FIG. 5 starts, when a frame F is transmitted from one of

09431001.011000

the frame relay networks FR1-FR3 to one of the IWFs 21a-21c. The frame transmission processing part 55 reads the transmitted frame relay network number out from the transmitted frame relay network number retrieval table 53 (see FIG. 9). The traffic control part 56 starts by receiving the transmitted frame relay network number, the DLCI number, and the process identifier information (receiving process information held the frame transmission processing part 55) from the frame transmission processing part 55. The frame transmission processing part 55 receives a notification requiring a discard or a notification requiring no discard of a frame F from the traffic control part 56, determines whether the frame F is discarded or not, and discards the frame F when it is determined that the frame F is discarded.

The frame reception processing part 57 starts when a frame F is received by one of the frame relay networks FR1-FR3 through one of the IWFs 21a-21c. The frame reception processing part 57 reads the transmitted frame relay network number out from the transmitted frame relay network number retrieval table 53 (see FIG. 9). The traffic control part 56 starts by receiving the transmitted frame relay network number, the DLCI number, and the process identifier information (receiving process information held the frame reception processing part 57) from the frame reception processing part 57.

05481001-011000

The traffic control part 56 starts by receiving a notification from the frame transmission processing part 55 or the frame reception processing part 57. The traffic control part 56 reads the restrictive class out from the restrictive class management table 50 (see FIG. 6). Successively, the traffic control part 56 operates the restrictive level based on the value stored in the restrictive threshold management table 51 (see FIG. 7). Then, the traffic control part 56 reads out the process task number from the task number storage table 54 by using the restrictive class and the restrictive level, and the traffic control part 56 performs the process task corresponding to the process task number.

The transmission data initializing part 58 starts every predetermined cycle and initializes contents in the transmission data cumulative table 52.

Next, an explanation will be given of processes by each frame relay switch 31a-31i with reference to flow charts shown in FIGs. 11-14. As a premise, when a frame is received by one of frame relay switches 31a-31i, the frame F is stored in the MM 34a through the LS 44, the LC 43a, the MP 42 and the CHC 35b.

As shown in FIG. 11, in the step S01, it is determined whether a frame is received or not. The step S01 is repeated until a frame F is received. That is, the step S01 is a state that a receipt of a frame F is waited, thereafter the process is advanced to the step

S02 when a frame F is received.

5 In the step S02, it is determined whether the frame F is received from one of the IWFs 21a-21c or not. This determination is performed by referring the circuit number (DLCI number) which receives the frame F in the step S01. When it is determined that the frame F is received from one of the IWFs 21a-21c, the process is advanced to the step S03. When it is not determined that the frame F is received from one of the IWFs 21a-21c, it is determined that the frame F is received from one of the terminals 22a-22h or another frame relay switch 31, thereafter the process is advanced to the step S04.

10 In the step S04, it is determined whether the frame F should be transmitted to one of the IWFs 21a-21c. This determination is performed by referring the circuit number (DLCI number) for transmitting the frame F similarly to the step S02. Then, when it is not determined that the frame should be transmitted to one of the IWFs 21a-21c, an usual process is performed in the step S14 and the frame F is transmitted to another frame relay switch or a terminal except for the transmitting terminal. When it is determined that the frame should be transmitted to one of the IWFs 21a-21c, thereafter the process is advanced to the step S05.

25 In the step S05, the frame transmission processing part 55 starts.

In the step S06, the frame transmission processing

09481001.011000

part 55 retrieves the transmitted frame relay network retrieval table 53 by using the DLCI number stored in the core header 27 of the frame F as a retrieval key and reads the transmitted frame relay network number.

5 In the step S07, the frame transmission processing part 55 informs the transmitted frame relay network number obtained in the step S06, the DLCI number, and the transmission process information which is the process identifier information the traffic control part
10 56. Then, the traffic control part 56 starts.

 In the step S08, the traffic control part 56 retrieves the restrictive class management table 50 (see FIG. 6) by using the transmitted frame relay network number received from the frame transmission processing
15 part 55 and the DLCI number as retrieval keys and reads out the restrictive class corresponding to the retrieval keys.

 In the step S09, the traffic control part 56 retrieves the restrictive threshold management table 51
20 (see FIG. 7) by using the transmitted frame relay network number received from the frame transmission processing part 55 as a retrieval key and operates the restrictive level by using each value stored correspondingly to the retrieval key. FIG. 12 is a flow
25 chart illustrating a traffic restrictive level operating subroutine performed in the step S09.

 In the step S101 in this subroutine, first, the

09431001-011000

traffic control part 56 retrieves the restrictive
threshold management table 51 by using the transmitted
frame relay network number received from the frame
transmission processing part 55 as a retrieval key and
5 reads out maxR, t1, n1, n2, n3 and n4 corresponding to
the retrieval key.

In the step S102, the traffic control part 56
retrieves the transmission data cumulative table 52 (see
FIG. 8) by using the transmitted frame relay network
10 number received from the frame transmission processing
part 55 as a retrieval key and reads out a cumulative
transmission data quantity (SD2) corresponding to the
retrieval key.

In the step S103, the traffic control part 56
15 calculates the transmission quantity of the frame F to
be transmitted to one of the IWFs 21a-21c by using the
following (expression 6);

$$\text{sd}(\text{bit}) = ([\text{transmission data} + 2 + 2 + 4] \div 48 + 1) \times 53 \times 8$$

...(expression 6).

20 In the (expression 6), the transmission data indicates
the number of octets of the core header 27 and the data
part 28 in the frame F to be transmitted to one of the
IWFs 21a-21c. The " $([\text{transmission data} + 2 + 2 + 4] \div 48 + 1)$ "
in the (expression 6) indicates the number of cells S
25 formed by disassembling the frame F. The " $\times 53$ " works out
the number of octets of all cells S (data quantity) when
a frame F is disassembled into plural cells S. The " $\times 8$ "

09481001-011000

converts the number of octets to the number of bits.

In the step S104, the traffic control part 56 adds the SD2 obtained in the step S102 to the sd obtained in the step S103. The added value becomes transmission data
5 quantity (SD) in the channel (data link) connecting between the frame relay network and the IWF ($SD2+sd=SD$).

In the step S105, the traffic control part 56 determines whether the ($SD2+sd$) satisfies the condition shown in the following (expression 7) or not;

10 $SD2+sd \leq \max R \times t1 \times n1$... (expression 7).

When the condition of the (expression 7) is satisfied, the operation is advanced to the step S106, and when the condition of the (expression 7) is not satisfied, thereafter the process is advanced to the step S107.

15 In the step S106, the traffic control part 56 determines that the $SD2+sd$ (SD) satisfies the condition of the (expression 1), namely, the restrict level is non-restriction, and the determined result is stored in the MM 34a. Thereafter, the process is advanced to the
20 step S114.

In the step S107, the traffic control part 56 determines whether the ($SD2+sd$) satisfies the condition shown in the following (expression 8) or not;

$SD2+sd \leq \max R \times t1 \times n2$... (expression 8).

25 When the condition of the (expression 8) is satisfied, the process is advanced to the step S108, and when the condition of the (expression 8) is not satisfied, the

operation is advanced to the step S109.

In the step S108, the traffic control part 56 determines that the (SD2+sd) satisfies the condition of the (expression 2), namely, the restrict level is the first restriction, and the determined result is stored in the MM 34a. Thereafter, the process is advanced to the step S114.

In the step S109, the traffic control part 56 determines whether the (SD2+sd) satisfies the condition shown in the following (expression 9) or not;

$$SD2+sd \leq \max R \times t1 \times n3 \quad \dots (\text{expression } 9).$$

When the condition of the (expression 9) is satisfied, the process is advanced to the step S110, and when the condition of the (expression 9) is not satisfied, the process is advanced to the step S111.

In the step S110, the traffic control part 56 determines that the (SD2+sd) satisfies the condition of the (expression 3), namely, the restrict level is the second restriction, and the determined result is stored in the MM 34a. Thereafter, the operation is advanced to the step S114.

In the step S111, the traffic control part 56 determines whether the (SD2+sd) satisfies the condition shown in the following (expression 10) or not;

$$SD2+sd \leq \max R \times t1 \times n4 \quad \dots (\text{expression } 10).$$

When the condition of the (expression 10) is satisfied, the process is advanced to the step S112, and when the

094E1001-011000

condition of the (expression 10) is not satisfied, the process is advanced to the step S113.

In the step S112, the traffic control part 56 determines that the (SD2+sd) satisfies the condition of the (expression 4), namely, the restrict level is the third restriction, and the determined result is stored in the MM 34a. Thereafter, the process is advanced to the step S114.

In the step S113, the traffic control part 56 stores the fourth restriction as a restrict level in the MM 34a. Thereafter, the process is advanced to the step S114.

In the step S114, the traffic control part 56 retrieves the transmission data cumulative table 52 (see FIG. 8) by using the transmitted frame relay network number as a retrieval key, and over writes the (SD+sd) as a new transmission data quantity (SD2) stored correspondingly to the retrieval key. At the same time, the traffic control part 56 over writes the restrictive level memorized in one of the steps S106, S108, S110, S112 and S113 as a new restrictive level to be stored. Thereafter, the process in the step S114 is finished, the process returns to the main routine in FIG. 11. In the main routine to which the process is returned, the step S10 is performed.

In the step S10, the traffic control part 56 retrieves the task number storage table 54 (see FIG. 10)

09441001.011000

by using the process identifier information
(transmission process information) received from the
frame transmission processing part 55, the restrictive
class obtained in the step S08 and the restrictive level
5 obtained in the step S09 as retrieval keys, and reads a
process task number (one of process tasks (1)-(4))
corresponding to the retrieval keys.

In the step S11, the traffic control part 56 starts
(performs) the process task corresponding to the process
10 task number read in the step 10. FIG. 13 is a flow chart
showing a process task starting subroutine performed in
the step 11. In the step S202 in this subroutine, the
traffic control part 56 determines whether the process
task number calculated in the step S09 is "(1)" or not.
15 When it is determined that the process task number is
"(1)", the process is advanced to the step S202. When it
is not determined that the process task number is "(1)",
the process is advanced to the step S203.

In the step S202, the traffic control part 56
20 performs the process task (1). That is, the traffic
control part 56 informs the frame transmission
processing part 55 that the frame F to be transmitted to
one of the IWFs 21a-21c is unnecessary to be discarded.
When the performance of the process task (1) is
25 finished, the process returns to the step S12.

In the step S203, the traffic control part 56
determines whether the process task number calculated in

09481001-011000

the step S09 is "(2)" or not. When it is determined that the process task number is "(2)", the process is advanced to the step S204. When it is not determined that the process task number is "(2)", the process is
5 advanced to the step S206.

In the step S204, the traffic control part 56 performs the process task (2). That is, "1" is set in the FECN of the core header 27 in the frame F to be transmitted to one of the IWFs 21a-21c. At the same
10 time, the traffic control part 56 informs the frame transmission processing part 55 that the frame F to be transmitted to one of the IWFs 21a-21c is unnecessary to be discarded. When the performance of the process task (2) is finished, the process returns to the step S12.
15 This process task (2) is performed, whereby a transmitted terminal (an user of a transmitted terminal) recognizes that a congestion occurs in the frame relay network FR1-FR3, and a congestion avoiding procedure (congestion control) is performed.

20 In the step S206, the traffic control part 56 determines whether the process task number calculated in the step S09 is "(2)" or not. When it is determined that the process task number is "(3)", the process is advanced to the step S207. When it is not determined
25 that the process task number is "(3)", the process is advanced to the step S211.

In the steps S207-S210, the traffic control part 56

09481001.011000

performs the process task (3).

That is, in the step S207, the traffic control part 56 determines whether "0" is set in the DE of the core header 27 in the frame F or not. When "0" is set in the DE, the process is advanced to the step S208. When "0" is not set in the DE (namely, DE=1), the process is advanced to the step S210.

In the step S208, the traffic control part 56 sets "1" in the FECN of the core header 27 in the frame F to be transmitted to one of the IWFs 21a-21c. With this arrangement, the transmitted terminal of the frame F performs a congestion avoiding procedure (congestion control), and the transmission of the frame F by the transmitted terminal is controlled.

In the step S209, the traffic control part 56 informs the frame transmission processing part 55 that the frame F to be transmitted to one of the IWFs 21a-21c is unnecessary to be discarded. When the step 209 is finished, the process returns to the main routine shown in FIG. 11.

In the step S210, the traffic control part 56 informs the frame transmission processing part 55 that the frame F to be transmitted to one of the IWFs 21a-21c is discarded. When the step 210 is finished, the process returns to the main routine shown in FIG. 11.

In the step S211, the traffic control part 56 determines whether the process task number calculated in

09481001 011000

5

10

15

In the step S13, the frame transmission processing part 55 discards the frame F to be transmitted to one of

the IWFs 21a-21c. With this arrangement, the number of cells transmitted from the IWFs 21a-21c to the ATM network 20 is decreased, and it is prevented that the number of cells exceeds the PCR. When the step S13 is finished, the process returns to the step S01 and accepts the next frame F.

In the step S14, an usual process is performed. That is, the frame F is transmitted through a suitable data link (one of the DLCIa-DLCIh) based on the DLCI number stored in the core header 27 of the frame F. Then, the process returns to the step S01 and accepts the next frame F.

On the contrary, when the process is advanced to the step S03, the frame receiving process is performed. FIG. 14 is a flow chart showing a frame receiving process subroutine performed in the step S03. In the step S301 in this subroutine, first, the frame reception processing part 57 starts.

In the step S302, the frame reception processing part 57 retrieves the transmitted frame relay network number retrieval table 53 (see FIG. 9) by using the DLCI number stored in the core header 27 of the frame F as a retrieval key, and reads the transmitted frame relay network number corresponding to the retrieval key.

In the step S303, the frame reception processing part 57 informs the traffic control part 56 of the transmitted frame relay network number obtained in the

step S302, the DLCI number and the process identifier information (reception process information) held therein so as to start the traffic control part 56.

5 In the step S304, the traffic control part 56
retrieves the restrictive class management table 50 (see
FIG. 6) by using the transmitted frame relay network
number and the DLCI number received from the frame
reception processing part 57 as retrieval keys, and
reads out a restrictive class corresponding to the
10 retrieval keys.

In the step S305, the traffic control part 56 retrieves the transmission data cumulative table 52 (see FIG. 8) by using the transmitted frame relay network number received from the frame reception processing part 57 as a retrieval key, and reads out a traffic restrictive level.

In the step S306, the traffic control part 56
retrieves the task number storage table 54 (see FIG. 10)
by using the process identifier of the reception process
received from the frame reception processing part 57,
the restrictive class obtained in the step S304 and the
restrictive level obtained in the step S305 as retrieval
keys, and reads out the process task number (one of the
process tasks (1), (5)) corresponding to the retrieval
keys.

In the step S307, the traffic control part 56 determines whether the process task number read in the

step S306 is "(1)" or not. When it is determined that the process task number is "(1)", the process is advanced to the step S308. When it is not determined that the process task number is "(1)", the process is
5 advanced to the step S309.

In the step S308, the traffic control part 56 performs the process task (1). That is, the traffic control part 56 informs the frame reception processing part 57 that the frame F received in the frame relay
10 switch is unnecessary to be discarded. Then, the step S308 is finished, the process returns to the main routine shown in FIG. 11 and the usual process is performed in the step S14.

In the step S309, the traffic control part 56
15 determines whether the process task number read in the step S306 is "(5)" or not. When it is determined that the process task number is "(5)", the process is advanced to the step S310. When it is not determined that the process task number is "(5)", the process
20 returns to the step S309 and the usual process is performed in the step S14.

In the steps S310, S311, the process task (5) is performed. That is, in the step S310, the traffic control part 56 sets "1" in the BECN of the core header
25 27 in the frame F received by the frame relay switch 31. With this arrangement, the transmitted terminal which receives the frame F recognizes that a congestion occurs

09481001 011000

in the frame relay network FR1-FR3, and performs the congestion avoiding procedure (congestion control). Thus, the transmission of the frame F from the transmitted terminal is controlled.

5 In the step S311, the traffic control part 56 informs the frame reception processing part 57 that the frame F received in the frame relay switch 31 is unnecessary to be discarded. Then, the step S311 is finished, the process returns to the main routine shown
10 in FIG. 11 and the usual process is performed in the step S14. Incidentally, since the traffic control part 56 informs the frame reception processing part 57 only that the frame F is unnecessary to be discarded, the frame is not discarded by the frame reception processing
15 part 57.

Now, the transmission data cumulative value (SD2) set in the transmission data cumulative table 52 and the restrictive level are initialized by the transmission data initializing part 58 every predetermined period.
20 That is, a transmitted frame relay network number is inputted into the transmission data initializing part 58 every predetermined period, whereby the transmission data initializing part 58 starts. The transmission data initializing part 58 retrieves the transmission data
25 cumulative table 52 by using the transmitted frame relay network number inputted thereto as a retrieval key, and then makes the transmission data quantity value (SD2)

09421001.011000

zero-clear and the restrictive level to be non-restriction. Additionally, the period which the same transmitted frame relay network number is inputted is set so as to be the same time as the measuring time (t1) set correspondingly to that transmitted frame relay network number in the restrictive threshold management table 51. Thus, the stored content in the transmission data cumulative table 52 is initialized every transmitted frame relay network number, namely, whenever the t1 corresponding to that network number passes.

Next, an explanation will be given of an operational sample in this network system with reference to FIG. 15. FIG. 15 is a sequence diagram illustrating an operational sample in a case that a frame F is transmitted and received between the terminal 22a and the terminal 22e.

Referring to FIG. 15, first, in each frame relay switch 31a, 31b, 31g in the frame relay network FR1, it is assumed that the transmission data initializing part 58 initializes the content in the transmission data cumulative table 52, which the content is stored correspondingly to the network number of the frame relay network FR2.

Then, it is assumed that after transmitting and receiving the frame F between the terminal 22a and the terminal 22e, a frame F_1 which is transmitted from the terminal 22a to the terminal 22e to be a transmitted

terminal is transmitted to the frame relay network FR1 (frame relay switch 31a).

The frame F_1 , as shown in FIG.2, is transmitted to the frame relay switch 31a through the DLC1a. At that
5 time, "0" to be an initialized value is set in the FECN of the core header 27 in the frame F_1 .

In the frame relay switch 31a, when the frame F_1 is received, the usual process is performed in the step S14 (see FIG. 11), and then the frame F_1 is transmitted to
10 the frame relay switch 31g through the DLC1a based on the DLCI number stored in the core header 27 thereof.

In the frame relay switch 31g, it is determined that the frame F_1 should be transmitted to the IWF 21a in the step S04. Then, the restrictive class is read in
15 the step S08, and the restrictive level is calculated in the step S09 (see FIG. 11). At that time, for example, when the first restriction is memorized as the restrictive level (step S108: see FIG. 12), the process task (2) is performed so as to set "1" in the FECN of
20 the core header 27 in the frame F_1 (step S204: see FIG. 13). Then, the usual process is performed in the step S14, whereby the frame F_1 is transmitted to the IWF 21a through the DLC1a.

In the IWF 21a, the frame F_1 is disassembled into
25 plural cells S_1 , and each cell S_1 is transmitted to the ATM network 20 via the VCCx₁.

In the ATM network 20, a transmitted destination of

03461607.011000

each cell S_1 is determined based on the VCI and the VPI (see FIG. 3) stored in the cell header 70 thereof, and then each cell S_1 is transmitted to the IWF 21b via the VCCy.

5 In the IWF 21b, the plural cells S_1 respectively received from the ATM network 20 are assembled into one frame F_1 . Then, the assembled frame F_1 is transmitted to the frame relay network FR2 (frame relay switch 31h) through the DLCIe based on the DLCI number stored in the
10 core header 27 thereof.

 In the frame relay switch 31h, it is determined that the frame F_1 is received from the IWF 21b in the step S02, and then the frame reception process is performed in the step S03. Incidentally, at that time,
15 it is assumed that the non-restriction is memorized as the restrictive level in the step S305 (see FIG. 14) and the process task (1) is performed. With this arrangement, no traffic restriction is performed, and the usual process is performed in the step S14, whereby
20 the frame F_1 is transmitted to the frame relay switch 31c.

 In the frame relay switch 31c, the usual process is performed in the step S14 after the steps S01-S04, and the frame F_1 is transmitted to the terminal 22e through
25 the DLCIe based on the DLCI number stored in the core header 27 thereof.

 When the terminal 22e receives the frame F_1 , the

0040310001-0110000

Thereafter, the terminal 22e generates a response frame f_1 to the frame F_1 , and then transmits the response frame f_1 to the frame relay network FR2 (frame relay switch 31c) in regarding the terminal 22a as a transmitted destination.

In the frame relay switch 31h, when the response frame f_1 is received and is determined to be transmitted to the IWF 21b, the traffic restrictive level is calculated in the step S09. Incidentally, it is assumed that the non-restriction is memorized in the step S106

(see FIG. 12) and the process task (1) is performed in the step S202 (see FIG. 13). Then, the usual process is performed in the step S14, and the response frame f_1 is transmitted to the IWF 21b through the DLC1e.

5 In the IWF 21b, the response frame f_1 is disassembled into plural cells s_1 , and then the plural cells s_1 are transmitted to the ATM network 20 through the VCCy.

10 In the ATM network 20, each cell s_1 is transmitted to the IWF 21a through the VCCx₁ based on the VPI and the VCI stored in the cell header 70.

15 In the IWF 21a, plural cells s_1 are assembled to one response frame f_1 . Then, the response frame f_1 is transmitted to the frame relay network FR1 (frame relay switch 31g) through the DLC1a based on the DLCI number stored in the core header 27 thereof.

20 In the frame relay switch 31g, when it is determined that the response frame f_1 is received from the IWF 21a, the frame reception process is performed in the step S03. That is, as shown in FIG. 14, the first restriction is memorized as the restrictive level in the step S305, and "1" is set in the BECN of the core header 27 in the step S310. Then, the usual process is performed in the step S14, the response frame f_1 is transmitted to the frame relay switch 31a.

25

In the frame relay switch 31a, the usual process is performed in the step S14, and the response frame f_1 is

transmitted to the terminal 22a.

09481001 "014000

In the terminal 22a, it is recognized that a congestion occurs in the frame relay network FR1 or FR2 based on that "1" is set in the BECN of the frame F_1 thereof, and then performs the congestion avoiding procedure (congestion control) so as to control the transmission of the frame F. With this arrangement, the transmission of frames F transmitted from the terminal 22a to the terminal 22e as a transmitted terminal is controlled. Thus, the number of cells S transmitted from the IWF 21a through the VCCx₁ decreases, and then it is prevented that the number of cells S exceeds the PCR.

Thereafter, when the measuring time t1 (stored in the restrictive threshold management table 51 correspondingly to the network number of the frame relay network FR2) passes, the network number of the frame relay network FR2 (transmitted frame relay network number) is inputted into the transmission data initializing part 58 (see FIG. 5). With this arrangement, the transmission data initializing part 58 starts, whereby the value SD2 which is stored in the transmission data cumulative table 52 (see FIG. 8) correspondingly to the network number of the frame relay network FR2 is made zero-clear and the non-restriction is set as the traffic restrictive level. The initialization is performed like this.

Thereafter, it is assumed that after receiving and

transmitting a frame F not shown between the terminal 22a and the terminal 22e, the terminal 22a transmits a frame F_2 which regards the terminal 22e as a transmitted terminal to the frame relay network FR1.

5 The frame F_2 is received by the frame relay switch 31g through the frame relay switch 31a in the frame relay network FR1. Then, the traffic restrictive level is calculated in the step S09 as above mentioned. Here, the process is advanced to the step S113 and the fourth
10 restriction is memorized as the restrictive level. When a discard is notified in the step S212, the frame F_2 is discarded in the step S13.

 When the measuring time t_1 passes again, the transmission data initializing part 58 starts. The
15 transmission data initializing part 58 initializes the value SD2 and the traffic restrictive level stored in the transmission data cumulative table 52 correspondingly to the network number of the frame relay network FR2. With this arrangement, the traffic
20 restriction corresponding to the DLC1a becomes the non-restriction from the fourth restriction.

 According to this embodiment, when a frame F is transmitted from one of the frame relay networks FR1-FR3 to one of the IWFs 21a-21c, or when a frame F (response
25 frame) is received from one of the IWFs 21a-21c to one of the frame relay networks FR1-FR3, a traffic restrictive class is detected and a traffic restrictive

09461001-014000

level corresponding to the transmission data quantity
(SD) is calculated, and then a process task
corresponding to the restrictive class and the
restrictive level is performed. The process task is
5 performed, whereby a congestion avoiding procedure
(congestion control) for the frame relay network FR1-FR3
is performed in a transmitting terminal and a
transmitted terminal of the frame F. Moreover, according
to the restrictive level, a frame F is discarded in one
10 of the frame relay networks FR1-FR3. Thus, there is no
case that the number of cells S transmitted to the ATM
network 20 exceeds a determined PCR.

Thus, it can be prevented that a cell S (frame F)
is discarded in the ATM network 20. According to this,
15 it is possible to avoid a congestion caused by that the
number of cells S exceeds the PCR in the frame relay
network FR1-FR3. Further, since the re-transmission of
the frame in the terminal 22a-22h can be reduced, it is
possible to lighten the process load in the frame relay
20 network FR1-FR3 and it is possible to avoid a response
deterioration of the communication from a terminal to a
terminal (end to end).

Additionally, a restrictive class can be set in
accordance with the importance of the DLCIa-DLCIh, and a
25 traffic restrictive process can be performed in
accordance with each restrictive class, therefore, it is
possible to discriminate each DLCI and to perform a

09481001.011000

traffic process more suitably.

In this embodiment, as shown in FIG. 2, data links (DLCI) between frame relay networks and IWFs and a VCC between the IWF and the ATM network are set in the ratio of N:1, however, a data link and a VCC may be set in the ratio of 1:1.

Each frame relay switch 31a-31i in this embodiment, when "1" is set in the BECN of the frame by performing a process task, may generate a CLLM (Consolidated Link Layer Management) message for notifying a congestion occurrence to a transmitting terminal of the frame and may transmit it to the transmitting terminal, and each frame relay switch may transmit a CLLM message to a transmitting terminal instead of setting "1" in the BECN.

In this embodiment, a restrictive class and a restrictive level are detected every transmitted frame relay network and a process task (1)-(5) is performed, however, a restrictive class and a restrictive level may be obtained every transmitting frame relay network and a process task corresponding to those may be performed. That is, one of the terminals 22e-22h in FIG. 1 may be directly connected to the IWFs 21b, 21c not through the frame relay networks FR2, FR3.

Moreover, the frame relay networks FR1-FR3 are respectively provided with the plural frame relay switches 31a-31i, however, the frame relay networks FR1-

09481001-011000

FR3 may be provided with one frame relay switch, namely, it is not necessary to care the number of frame relay switches in a frame relay network.

Further, it is possible to vary the measuring time
5 t1. For example, the above-mentioned traffic process may be performed at a real time.

According to a traffic control method, a network system and a frame relay switch of the present invention, it can be prevented that the number of cells
10 transmitted to an ATM network exceeds a maximum transmission rate. Thus, it can be prevented that cells are discarded caused by that the number of cells exceeds the maximum transmission rate and a congestion occurs in frame relay networks.

15 This invention being thus described, it will be obvious that same may be varied in various ways. Such variations are not to be regarded as departure from the spirit and scope of the invention, and all such modifications would be obvious for one skilled in the art intended to be included within the scope of the
20 following claims.

09481001.01.1000